

Drill Press

ZJ4113 II Drill Press



Motor: 120v - , 60Hz, 2.7A

Max. Drilling Capacity: Φ 13mm

Spindle Travel: 50mm

Spindle Taper: MT2#

Column Diameter: Φ 50mm

Spindle Speed: 5 Speeds: 580 - 2650 RPM

5 Speeds: 760 - 3100 RPM

Max. Distance From Spindle Axis to Surface of Column: 102mm

Max. Distance From Spindle End to Surface of table: 250mm

Table Size: Main Table Size: 152 X 170mm

With Extension Table Size: 192(Max 272mm) X 170mm

Base Size: 320 X 190mm

Exterior Size: 410 X 240 X 650mm

Packing Size: 570 X 377 X 260mm

G.W/N.W.: 25.6/24Kgs

Loading Amount: 480PCS/20';

ZJ4116 IIA Drill Press



Motor: 120v - , 60Hz, 4.2A

Max. Drilling Capacity: Φ 16mm

Spindle Travel: 65mm

Spindle Taper: MT2#

Column Diameter: Φ 60mm

Spindle Speed: 12 Speeds: 525 - 2545 RPM

12 Speeds: 510 - 3140 RPM

Max. Distance From Spindle Axis to Surface of Column: 126mm

Max. Distance From Spindle End to Surface of table: 355mm

Max. Distance From Spindle End to Surface of base: 465mm

Table Size: Main Table Size: 200 X 200mm

With Extension Table Size: 240(Max 330mm) X 200mm

Base Size: 380 X 250mm

Exterior Size: 520 X 300 X 850mm

Packing Size: 712 X 430 X 315mm

G.W/N.W.: 43/39.5Kgs

Loading Amount: 290PCS/20';

ZJ4113A Drill Press



Motor: 120v - , 60Hz, 2.5A

Max. Drilling Capacity: Φ 13mm

Spindle Travel: 50mm

Spindle Taper: MT2#

Column Diameter: Φ 46mm

Spindle Speed: 5 Speeds: 580 - 2650 RPM

5 Speeds: 760 - 3070 RPM

Max. Distance From Spindle Axis to Surface of Column: 104mm

Max. Distance From Spindle End to Surface of table: 200mm

Max. Distance From Spindle End to Surface of base: 290mm

Table Size: Main Table Size: 160 X 160mm

Base Size: 314 X 200mm

Exterior Size: 355 X 225 X 580mm

Packing Size: 440 X 335 X 225mm

G.W/N.W.: 20/19Kgs

Loading Amount: 850PCS/20';

ZJ4113C Drill Press



Motor: 120v - , 60Hz, 2.5A

Max. Drilling Capacity: Φ 13mm

Spindle Travel: 50mm

Spindle Taper: MT2#

Column Diameter: Φ 46mm

Spindle Speed: 5 Speeds: 760 - 3070 RPM

Max. Distance From Spindle Axis to Surface of Column: 104mm

Max. Distance From Spindle End to Surface of table: 200mm

Max. Distance From Spindle End to Surface of base: 290mm

Table Size: Main Table Size: 160 X 160mm

Base Size: 291 X 183mm

Exterior Size: 445 X 225 X 590mm

Packing Size: 460 X 350 X 265mm

G.W/N.W.: 20/19Kgs

Loading Amount: 640PCS/20';



ZJ4116 Drill Press

Moter: 120v - , 60Hz, 6.6A

Max. Drilling Capacity: Φ 16mm

Spindle Travel: 80mm

Spindle Taper: MT2#

Column Diameter: Φ 70mm

Spindle Speed: 12 Speeds: 210 - 2220 RPM

Spindle Speed: 16 Speeds: 210 - 3840 RPM

Max. Distance From Spindle Axis to Surface of Column: 169mm

Max. Distance From Spindle End to Surface of table: 390mm

Max. Distance From Spindle End to Surface of base: 640mm

Table Size: Φ 290mm

Base Size: 250 X 434mm

Exterior Size: 600 X 350 X 990mm

Packing Size: 800 X 490 X 275mm

G.W/N.W.: 56/53Kgs

Loading Amount: 260PCS/20';



ZJ4116H Drill Press

Moter: 120v - , 60Hz, 6.6A

Max. Drilling Capacity: Φ 16mm

Spindle Travel: 80mm

Spindle Taper: MT2#

Column Diameter: Φ 70mm

Spindle Speed: 12 Speeds: 210 - 2220 RPM

Spindle Speed: 16 Speeds: 210 - 3840 RPM

Max. Distance From Spindle Axis to Surface of Column: 169mm

Max. Distance From Spindle End to Surface of table: 780mm

Max. Distance From Spindle End to Surface of base: 1210mm

Table Size: 270 X 270mm

Base Size: 273 X 456mm

Exterior Size: 600 X 350 X 1570mm

Packing Size: 1145 X 465 X 270mm

G.W/N.W.: 63/60Kgs

Loading Amount: 192PCS/20';