

High Tensile Steel Strapping

Code	Width		Thickness		Average Strength		Length/Weight		Average Coil Weight	
	inches	mm	inches	mm	lbs	(N)	ft/lbs	m/kg	lbs	(kg)
HT1220	1/2	12.7	0.020	0.51	1500	6670	29.4	19.8	100-105	45-47
HT1223	1/2	12.7	0.023	0.58	1725	7670	25.6	17.2	100-105	45-47
HT5820	5/8	15.9	0.020	0.51	1875	8340	23.5	15.9	100-105	45-47
HT5823	5/8	15.9	0.023	0.58	2150	9560	20.5	13.8	100-105	45-47
HT3420	3/4	19.0	0.020	0.51	2250	10000	19.6	13.2	100-105	45-47
HT3423	3/4	19.0	0.023	0.58	2600	11560	17.1	11.5	100-105	45-47
HT3425	3/4	19.0	0.025	0.64	2800	12450	15.7	10.5	100-105	45-47
HT3429	3/4	19.0	0.029	0.74	3320	14770	13.5	9.0	100-105	45-47
HT3431	3/4	19.0	0.031	0.79	3500	15560	12.7	8.5	100-105	45-47
HT3435	3/4	19.0	0.035	0.89	3900	17350	11.2	7.5	100-105	45-47
HT3444	3/4	19.0	0.044	1.12	4950	22020	8.71	5.9	100-105	45-47
HT11425	1-1/4	32.0	0.025	0.64	4650	20680	9.4	6.3	100-105	45-47
HT11431	1-1/4	32.0	0.031	0.79	5500	24460	7.6	5.1	100-105	45-47
HT11435	1-1/4	32.0	0.035	0.89	5800	25800	6.72	4.5	100-105	45-47
HT11444	1-1/4	32.0	0.044	1.12	8350	37140	5.35	3.6	100-105	45-47
HT244	2	51	0.044	1.12	12300	54710	3.34	2.2	100-105	45-47
HT250	2	51	0.050	1.27	14000	62270	2.94	2.0	100-105	45-47
Other sizes & strength available										

